



TORBO L120

\$38,500.00

Description

Complete with torbo L120 unit, 25x40mm 20m blast hose with #6 blast nozzle, 25m deadman cable and 2 stage handle. The special feature of the torbo L120 is its many and diverse types of use. This system, specially designed for all-round requirements, distinguishes itself in everyday use. The careful removal of even stubborn encrustations from sensitive surfaces belongs to its scope of application as does the removal of concrete sludge and paint coatings or after-fire remedial action. With integrated quick switch-off, switch-over blasting/ washing or ATEX version, you can configure the device according to your requirements.

Specifications:

Tank Size: 120 L or 240 L Power Supply: 12 V Compressed Air Connection: 1 1/2" Compressed Air Supply: up to 10 m³/min (353 CFM/min) Blasting Hose Connection: 1 1/2" Blasting Media Consumption: 14.4-384 L/hour Standard Blasting Mixture: 80% (Media) : 20% (Water) Water Consumption During Blasting: 3.6-96 L/hour Dimensions: 660 x 830 x 1240mm (120L model) Empty Weight: 140-185 kg Control Pressure: 174 psi

Page 1



Contact us today to find out more.

Perth Head Office: (08) 9309 1599 Melbourne: 0437 722 272 Sydney: 0429 087 181